



Specifications:
 Current Rating:1.5A AC/DC **0.5A**
 Voltage Rating:30V AC/DC
 Contact Resistance:30m ohm. Max.
 Insulation Resistance:1,000M ohm. min.
 Withstanding Voltage:750V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish **-55 ~ 85°C**
 Insulator:PBT(UL94V-0) **PA6T**
 Insulator Color:Black
 Contact:Brass **Phosphor Bronze**
 Plating:Gold Flash Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Brass,Nickel Plated

Shell:Phosphor Bronze or SK7
Rear Shell:SPCC

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.25 ±0.20 .XX=±0.20 ±0.15	<h1 style="text-align: center; color: red;">CnC Tech</h1> <p style="text-align: center;">Industrial Cable and Connector Technology</p>		
				CHECKED:	UNIT: MM			DESCRIPTION: USB A Type PCB Socket Right Angle,G/F
					SCALE:1:1	PART NO:	A4	
	05-FEB-2020			APPROVAL:	SHEET: 1 / 2	1001-007-01020		
REV	DATE	FILE	BY		PROJECTION:			

A
B
C
D