



Specifications:  
 Current rating:1.0A AC/DC  
 Voltage rating:250V AC/DC  
 Contact resistance:20m ohm max. **20M ohm**  
 Withstanding Voltage:500V AC/minute  
 Insulation resistance:1000M ohm min.  
 Temperature Rating:-40°C ~ +105°C  
 Materials:  
 Insulator:PBT (UL94V-0)  
 Standard Color:Black  
 Contact:Copper Alloy **Brass**  
 Finish:Selective Gold Plated  
**Gold Flash over Nickel**

Circuits	Dim				Circuits	Dim			
	A	prior 20/06	B	prior 20/06		A	prior 20/06	B	prior 20/06
8	7.62	7.62	14.84	14.86	26	30.48	30.48	37.70	37.72
10	10.16	10.16	17.38	17.40	30	35.56	35.56	42.78	42.80
12	12.70	12.70	19.92	19.94	34	40.64	40.64	47.86	47.88
14	15.24	15.24	22.46	22.48	36	43.18	43.18	50.40	50.42
16	17.78	17.78	25.00	25.02	40	48.26	48.26	55.48	55.50
18	20.32	20.32	27.54	27.56	44	53.34	53.34	60.56	60.58
20	22.86	22.86	30.08	30.10	50	60.96	60.96	68.18	68.20
22	25.40	25.40	32.62	32.64	60	73.66	73.66	80.88	80.90
24	27.94	27.94	35.16	35.18	64	78.74	78.74	85.96	85.98

Note: Dimension in red represents old dimension

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 ±0.25 .XX=±0.15 ±0.20	<h1 style="text-align: center; color: red;">CnC Tech</h1> <p style="text-align: center;">Industrial Cable and Connector Technology</p>		
				CHECKED:	UNIT: MM SCALE:1:1			DESCRIPTION: 2.54MM Flat Cable IDC Socket With Strain Relief
				APPROVAL:	SHEET: 1 / 2	PART NO:	A4	
REV	DATE	FILE	BY		PROJECTION:	3030-XX-0103-00		