

PART NUMBER	DESCRIPTION	STRENGTH and LENGTH INFORMATION	TEMPERATURE RESISTANCE
109-80M-001	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 15mm (0.591 inch) Length: 80mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-80M-002	NYLON CABLE TIE, PA66	Min Loop tensile: 8Kg (18Ibs) Max bundle dia.: 15mm (0.591 inch) Length: 80mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-100M-001	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 100mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-100M-002	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 100mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-120M-001	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 28mm (1.102 inch) Length: 120mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-120M-002	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 28mm (1.102 inch) Length: 120mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-165M-001	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 43mm (1.692 inch) Length: 165mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-165M-002	NYLON CABLE TIE, PA66	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 43mm (1.692 inch) Length: 165mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-140I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 33mm (1.299 inch) Length: 142mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-140I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 33mm (1.299 inch) Length: 142mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-150I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 35mm (1.377 inch) Length: 150mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-150I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 35mm (1.377 inch) Length: 150mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-200I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 52mm (2.047 inch) Length: 203mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-200I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 52mm (2.047 inch) Length: 203mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-250I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 65mm (2.559 inch) Length: 250mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-250I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 65mm (2.559 inch) Length: 250mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-300I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 76mm (2.992 inch) Length: 300mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)
109-300I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 76mm (2.992 inch) Length: 300mm±0.5, NATURE	-4 F (-20°C) to 185 F (85 °C)
109-370I-001	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 368mm±0.5, BLACK	-4 F (-20°C) to 185 F (85 °C)

109-370I-002	NYLON CABLE TIE, PA66	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 368mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-120S-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 120mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-120S-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 120mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-190S-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 46mm (1.811 inch) Length: 190mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-190S-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 46mm (1.811 inch) Length: 190mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-250S-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 65mm (2.559 inch) Length: 250mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-250S-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 65mm (2.559 inch) Length: 250mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-300S-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 80mm (3.149 inch) Length: 300mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-300S-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 80mm (3.149 inch) Length: 300mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-385S-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 105mm (4.133 inch) Length: 385mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-385S-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 105mm (4.133 inch) Length: 385mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-160SD-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 42mm (1.653 inch) Length: 160mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-160SD-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 42mm (1.653 inch) Length: 160mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-200SD-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 55mm (2.165 inch) Length: 203mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-200SD-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 55mm (2.165 inch) Length: 203mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-250SD-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 74mm (2.913 inch) Length: 250mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-250SD-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 74mm (2.913 inch) Length: 250mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-300SD-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 80mm (3.149 inch) Length: 300mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-300SD-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 80mm (3.149 inch) Length: 300mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)
109-370SD-001	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 368mm±0.5, BLACK	-4 F (-20° C) to 185° F (85° C)
109-370SD-002	NYLON CABLE TIE, PA66	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 368mm±0.5, NATURE	-4 F (-20° C) to 185° F (85° C)

109-370H-001	NYLON CABLE TIE, PA66	Min loop tensile: 54Kg (120Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 370mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-370H-002	NYLON CABLE TIE, PA66	Min loop tensile: 54Kg (120Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 370mm±0.5, NATURE	-4° F (-20° C) to 185° F (85° C)
109-450L-001	NYLON CABLE TIE, PA66	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 124mm (4.881 inch) Length: 450mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-450L-002	NYLON CABLE TIE, PA66	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 124mm (4.881 inch) Length: 450mm±0.5, NATURE	-4° F (-20° C) to 185° F (85° C)
109-610L-001	NYLON CABLE TIE, PA66	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 175mm (6.889 inch) Length: 610mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-610L-002	NYLON CABLE TIE, PA66	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 175mm (6.889 inch) Length: 610mm±0.5, NATURE	-4° F (-20° C) to 185° F (85° C)
109-152S-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 45.4Kg (100Ibs) Max bundle dia.: 25mm (0.984 inch) Length: 152mm±0.5, BLACK COATING	112° F (-80° C) to 1000° F (538° C)
109-200M-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 113.4Kg (250Ibs), Max bundle dia.: 50mm (1.968 inch) Length: 200mm±0.5, BLACK COATING	112° F (-80° C) to 1000° F (538° C)
109-300S-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 45.4Kg (100Ibs) Max bundle dia.: 75mm (2.952 inch) Length: 300mm±3.0, BLACK COATING	112° F (-80° C) to 1000° F (538° C)
109-520M-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 113.4Kg (250Ibs) Max bundle dia.: 152mm (5.984 inch) Length: 520mm±0.5, BLACK COATING	-40° F (-40° C) to 248° F (120° C)
109-152M-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 113.4Kg (250Ibs) Max bundle dia.: 25mm (0.984 inch) Length: 152mm±0.5	112° F (-80° C) to 1000° F (538° C)
109-200M-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 113.4Kg (250Ibs) Max bundle dia.: 60mm (2.362 inch) Length: 200mm±3.0	112° F (-80° C) to 1000° F (538° C)
109-200S-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 45.4Kg (100Ibs) Max bundle dia.: 50mm (1.968 inch) Length: 200mm±0.5	112° F (-80° C) to 1000° F (538° C)
109-300S-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 45.4Kg (100Ibs) Max bundle dia.: 75mm (2.952 inch) Length: 300mm±3.0	112° F (-80° C) to 1000° F (538° C)
109-360M-STB	STAINLESS STEEL (316) TIE, W/BALL LOCK	Min loop tensile: 113.4Kg (250Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 360mm±0.5	112° F (-80° C) to 1000° F (538° C)
109-UV80M-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 15mm (0.591 inch) Length: 80mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-UV100M-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 8Kg (18Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 100mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-UV140I-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 33mm (1.299 inch) Length: 142mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-UV200I-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 52mm (2.047 inch) Length: 203mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-UV300I-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 18Kg (40Ibs) Max bundle dia.: 76mm (2.992 inch) Length: 300mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)
109-UV120S-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 22mm (0.866 inch) Length: 120mm±0.5, BLACK	-4° F (-20° C) to 185° F (85° C)

109-UV250S-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 65mm (2.559 inch) Length: 250mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)
109-UV300S-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 80mm (3.149 inch) Length: 300mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)
109-UV160SD-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 22Kg (50Ibs) Max bundle dia.: 42mm (1.653 inch) Length: 160mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)
109-UV370H-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 54Kg (120Ibs) Max bundle dia.: 102mm (4.015 inch) Length: 370mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)
109-UV450L-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 124mm (4.881 inch) Length: 450mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)
109-UV610L-001	NYLON CABLE TIE, PA66 - UV TYPE	Min loop tensile: 80Kg (175Ibs) Max bundle dia.: 175mm (6.889 inch) Length: 610mm±0.5, BLACK	-4 °F (-20 °C) to 185 °F (85 °C)